

Easy loading and unloading of long and bulky parts.

kippLIFT

The work table "kippLIFT" facilitates the transport of long, heavy and bulky parts such as doors, kitchen counters, panel material, by easy loading and unloading.

The base structure of the "Lift Table 300 XL" remains the same with all its benefits - a smooth-running movable frame for easy handling, a pedal system operated lifting system with 300 kg load capacity and the individually adjustable working height between 740 - 1,300 mm - and is extended by a smooth-running tilting system. This makes it possible to pivot the worktop of the table by 89° lengthwise. The powerful gas springs support the crank drive and allow workpieces to tilt effortlessly.

For long workpieces, a 555 mm long pull-out is provided on both sides. The wide stop angle provided on one side is used to easily hold the workpieces in the tilted state. This allows to move bulky workpieces from the vertical to the horizontal position without any help.



Base version kippLIFT

3 different variants are available! – ask us!

- 2 steering rollers with brake Ø 125 mm
- 2 steering rollers with direction lock Ø 125 mm
- Folding stop bar
- Height adjustment on both longitudinal sides with foot pedals
- Tilting function up to 70 kg using a folding manual crank
- 1x rigging strap for attaching the workpiece
- Load capacity up to 300 kg
- Longitudinal pull-out by on both sides by 555 mm each
- Large height adjustment range: 740–1,300 mm
- Swivelling range 0–89°
- Footprint L x W x H: 2,240–3,350 x 1,020 x 740–1,300 mm

Lateral stop angle



*Ergo-
nomic*

- **Worktop**
1,015 x 2,240 mm, can be extended
to 1,015 x 3,350 mm by longitudinal pull-outs
- **Foot-pumped hydraulic system**
on both sides, operated on both
longitudinal sides

User video




Instant information at:

+49 8621 5050 600 or
info@barth-maschinenbau.de

Available worktops

- Hole plate
- Hole plate, HPL coated



Heavy weights very light

kippLIFT pro

Inspired by the "kippLIFT" assembly table, BARTH expands the concept of tipping long and bulky workpieces up to 225 kg and presents the "kippLIFT pro as a solution for assembly, storage and logistics.

Based on the "H 850 lifting table", the "kippLIFT pro" with its swivelling work surface and its powerful linear drive moves heavy workpieces up to 225 kg from the horizontal to the vertical position at the touch of a button. Secured by clamping options that can be used on the upper frame, various loads can be moved, assembled and loaded without any risk for the workpiece and the employees.



Base version kippLIFT pro

- 2 steering rollers with brake Ø 150 mm
- 2 castors Ø 150 mm
- Electrical tilting function with linear drive 12 V
- Hydraulic height adjustment by foot pump
- 1 rigging strap for attaching the workpiece

Course of the tilting process



Technical features:

- Max. lifting capacity of lifting table 800 kg
- Max. tilting load of tilting device 225 kg
- Large height adjustment range 560 – 1,200 mm
- Tilting function by handheld remote control
- Swivelling range 0–85°
- Footprint L x W x H: 2,100 x 1300 x 560– 1,200 mm

NEW!



Instant information at:

+49 8621 5050 600 or
info@barth-maschinenbau.de